



GERMAN TECHNOLOGY-GERMAN INNOVATION

Service Car Technology Vertriebs GmbH Hasenkamp. 4 22880 Wedel/Hamburg Germany

QUALITY CERTIFICATE

Senfineco GearUltra AG60 ATF

Properties

GearUltra AG60 ATF is a high-performance automatic transmission fluid developed for modern 8-speed automatic transmissions. Its advanced formulation provides excellent load-carrying capacity and outstanding wear reduction, even under high mechanical stress. Superior friction stability ensures smooth, precise and sporty gear changes. **GearUltra AG60 ATF** delivers excellent low-temperature shifting behaviour, reliable protection against foam formation and minimal evaporation losses. High oxidation and thermal stability, combined with neutrality towards common sealing materials, ensure long service life and consistently high transmission performance.

Application notes

GearUltra AG60 is especially designed for modern ZF 6-, 8- and 9-speed automatic transmissions used in high-performance passenger vehicles. **GearUltra AG60** is not suitable for use in double-clutch (DCT/DSG) or continuously variable (CVT) transmissions. **Observe manufacturer's instructions!**

Service description

Recommendations*:

- BMW L12108 (83 22 2 152 426)
- BMW L12108 (83 22 2 305 397)
- BMW 83 22 2 289 720 (ATF3+)
- Chrysler 68157995AA
- Honda Type 3.1
- Jaguar 02JDE 26444
- Land Rover LR 023288 / 232289

- Mopar 68157995AA
- VW / Audi G 060 162 A1/A2/A6
- VW / Audi G 055 162 (A2,A6)
- VW / Audi G 055 540 (A2)
- ZF Lifeguardfluid 8 (S671 090 312)
- ZF Lifeguardfluid 9 (AA01.500.001)

TYPICAL PARAMETERS	METHODS	UNITS	GearUltra AG60
Density at 15°C	DIN 51 757	kg/m ³	844
Viscosity at 40°C	DIN 51 562	mm ² /s	26.9
Viscosity at 100°C	DIN 51 562	mm ² /s	5.6
Viscosity Index (VI)	DIN ISO 2909	-	157
Pour point	DIN ISO 3016	°C	-45
Flash point COC	DIN ISO 2592	°C	224
Colour	-	-	green

* meets the requirements of the OEM manufacturer

The above values may vary within commercially accepted tolerances

December 2024