



GERMAN TECHNOLOGY-GERMAN INNOVATION

Service Car Technology Vertriebs GmbH Hasenkamp. 4 22880 Wedel/Hamburg Germany

QUALITY CERTIFICATE

Senfineco SynthPro 5W-30 SP ILSAC: GF-6A

Properties

SynthPro 5W-30 is an ultra high performance engine oil. It is designed to exceed the global gasoline engine specification of GM dexos1™ Gen 2.

SynthPro 5W-30 has a new improved formulation to protect against damage caused by engine knocking in gasoline direct injection engines with and without turbocharging. The composition of the oil minimises the probability of early ignition (LSPI, Low Speed Pre-Ignition). Extended oil change intervals according to manufacturer's instructions. Extreme loads and high temperatures are safely mastered.

SynthPro 5W-30 can be used under all operating conditions and contributes to the protection of the environment by reducing pollutant emissions.

Application notes

SynthPro 5W-30 is recommended for year-round use in petrol, ethanol (up to E85), propane and natural gas engines.

SynthPro 5W-30 can also be used for all older ILSAC and API performance classes including ILSAC GF-5, API SN and SN PLUS.

The product is not suitable for diesel engines.

Service description

Specifications:

- API SP
- ILSAC GF-6A

Recommendations*:

- GM dexos1™ Gen 2
- Chrysler MS-6395
- Ford WSS-M2C946-A
- Honda
- Hyundai
- Kia
- Mazda

TYPICAL PARAMETERS	METHODS	UNITS	SynthPro 5W30
Density at 15°C	ASTM D4052	kg/m³	845
Viscosity at 40°C	ASTM D445	mm²/s	64.1
Viscosity at 100°C	ASTM D445	mm²/s	11.3
Viscosity index (VI)	ASTM D2270	-	171
Pour point	ASTM D5950	°C	-45
Flash point COC	ASTM D92	°C	224
Base number	ASTM D2896	mg KOH/g	8.0
Sulphated ash	ASTM D874	Weight %	0.94

* meets the requirements of the OEM manufacturer
The above values may vary within commercially accepted tolerances

Service Car Technology Vertriebs GmbH
Hasenkamp 4 22880 Wedel

December 2024

Mobil: 0174 198 7145
Tel: 04103 9672761