



GERMAN TECHNOLOGY-GERMAN INNOVATION

Service Car Technology Vertriebs GmbH Hasenkamp. 4 22880 Wedel/Hamburg Germany

QUALITY CERTIFICATE

Senfineco SynthUltra 0W-40 SN A3/B4

Properties

SynthUltra 0W-40 is a high-performance low-friction engine oil based on synthetic technology meeting the most stringent requirements of modern turbocharged and non-turbocharged petrol and diesel engines in passenger cars. Excellent flow properties guarantee optimum cold start behaviour. Thanks to its unrivalled high-temperature stability, the product provides a reliable lubricant film even under extreme conditions. As it significantly reduces the fuel consumption, **SynthUltra 0W-40** helps protect the environment.

Application notes

SynthUltra 0W-40 is a top product for modern petrol and diesel engines in passenger cars with or without turbocharger.

Service description

Specifications:

- API SN/CF
- ACEAA3/B3, A3/B4

Recommendations*:

- Porsche A40
- BMW Longlife-01
- MB 226.5
- VW standards 502 00/505 00
- Renault RN 0700/RN 0710
- Fiat 9.55535-Z2
- Ford WSS-M2C937-A

Approvals:

- MB approval 229.5

TYPICAL PARAMETERS	METHODS	UNITS	SynthUltra 0W40
Density at 15°C	DIN 51 757	kg/m ³	845
Viscosity at 40°C	DIN 51 562	mm ² /s	74.8
Viscosity at 100°C	DIN 51 562	mm ² /s	13.4
Viscosity at -35°C	DIN 51 377	mPa.s	6120
Viscosity Index (VI)	DIN ISO 2909	-	185
Pour point	DIN ISO 3016	°C	-54
Flash point COC	DIN ISO 2592	°C	235
TBN	DIN ISO 3771	mg KOH/g	10.2

* meets the requirements of the OEM manufacturer
The above values may vary within commercially accepted tolerances